

KING DRAINS®

End of Line / Valve Protector Drains

Installation Instructions

All King Drains can be installed with or without a gravel sump. For small diameter shorter lines, a sump is not necessary. Larger and longer lines will drain more efficiently with a gravel sump. Install all King Drains on a 45° angle to ensure proper drainage of water from the pipe.

All End of Line Drains feature the new Soft Grip Drain.

For elevation changes greater than 15 feet, install one King Drain at each 15-foot interval.

* PVC End of Line Drain w/Soft Grip Installation:



1. Apply primer and cement to pipe and fitting.



2. Slide drain on pipe and twist.



3. Align at 45° angle for optimum drainage.

U.S. Patent Numbers 4,890,640, 5,080,527, 6,886,585 and D568,450. All other trademarks, U.S. and Foreign Patents Pending Apply. All Rights Reserved.

KING
INNOVATION®

Poly End of Line Drain w/Soft Grip

Catalog #	Size	Selling Unit
15140	3/4" x 1/2" FPT	Bag of 10
16142	1" x 1/2" FPT	Bag of 10
17145	1" x 3/4" FPT	Bag of 10



PVC End of Line Drain w/Soft Grip*

Catalog #	Size	Selling Unit
18142	1" x 1/2" PVC FPT	Bag of 5



Valve Protector†

Catalog #	Size	Selling Unit
21155	1" MPT x 1" INS	Bag of 5

† Does not have Soft Grip Design



50100-31 REV B 10/10

www.kinginnovation.com
(P) 800.633.0232
(F) 636.519.5410