



Siphon King Gas Powered Pump

Instructions

Please refer to Owner's Manual for complete operating instructions.

- 4-cycle, single cylinder, air-cooled gasoline engine
- Excellent for high volume water transfer
- Unrestricted flow 40 gallons per minute
- 1" inlet/outlet diameter
- Includes two (2) 6' hoses for intake and discharge, garden hose adapter, and strainer



Back

Siphon King® Gas Powered Pump

| Catalog # | Item | Selling Unit |
|-----------|------------------|--------------|
| 48350 | Gas Powered Pump | 1 per box |



Front

Parts Included



- A - 6' Hose
- B - Oil
- C - Strainer
- D - Garden Hose Adapter
- E - Large O-Ring Seal (Garden Hose Adapter)
- F - Hose Adapter #2
- G - Wrench
- H - Small O-Ring Seal (Hose)
- I - Hose Adapter #1
- J - Hose Clamps



Siphon King Gas Powered Pump

Siphon King® Gas Powered Pump

| Siphon King® Gas Powered Water Pump - Technical Specifications | |
|--|-------------------------------------|
| General | |
| Product Name | Siphon King® Gas Powered Water Pump |
| Model Number (SKU) | 48350 |
| Length | 11.5" |
| Width | 11.5" |
| Height | 13" |
| Weight | 18.9 lbs |
| Packaging Dimension | 16.5" x 12.6" x 14.6" |
| Engine | |
| Engine Type | 4-Cycle, Single Cylinder |
| Displacement | 40 cc |
| Cooling System | Air Cooled |
| Ignition System | Transistor Magneto |
| Starting System | Recoil Starter |
| Operating Mode | Continuous Operation |
| Engine Oil | SAE 10W-30 or 10W-40 API SM |
| Engine Oil Capacity | 2.7 oz |
| Fuel | Unleaded; 86 or higher |
| Fuel Tank Capacity | 0.2 US gal |
| Spark Plug Gap | 0.024" |
| Idle Speed | 3,300 ± 100 r/min |
| Pump | |
| Suction Port Diameter | 1.0" |
| Discharge Port Diameter | 1.0" |
| Max. Total Head | 82 ft |
| Max. Suction Head | 25 ft |
| Discharge Capacity | 39.6 gal/min (max) |