

Accessories

Black Cable Ties

76108 - 8" Cable Tie

Tensile Strength: 50 lbs/22 kgs
Max Bundle Diameter: 1.95"
Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon

76111 - 11" Cable Tie

Tensile Strength: 50 lbs/22 kgs
Max Bundle Diameter: 3.15"
Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon

76114 - 14" Cable Tie

Tensile Strength: 50 lbs/22 kgs
Max Bundle Diameter: 4.05"
Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon

76118 - 18" Cable Tie

Tensile Strength: 175 lbs/79 kgs
Max Bundle Diameter: 5.15"
Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon

76124 - 24" Cable Tie


Tensile Strength: 175 lbs/79 kgs
Max Bundle Diameter: 7.15"
Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon

77108 - 8" Cable Tie w/Screw Mount

Tensile Strength: 50 lbs/22 kgs
Max Bundle Diameter: 1.95"
Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon

78001 - Cable Mount

Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon



Black Cable Ties

Catalog #	Size	Selling Unit
76108	8"	100/bag
76111	11"	100/bag
76114	14"	100/bag
76118	18"	50/bag
76124	24"	50/bag
77108	8" w/Screw Mount	100/bag
78001	Cable Mount	100/bag

- Easy to use ties for landscape lighting on decks or trees, home, electrical, or any fastening needs
- Self-locking, one-piece, low profile head conserves space
- For maximum comfort, smooth rounded edges will not cut hands or insulation
- Rated for indoor and outdoor use
- UV Resistant
- Available in 8", 11", 14", 18" and 24" sizes
- 8" cable tie available with or without screw mount head
- 1" x 1" adhesive black cable mount available



Accessories

Nylon Cable Ties

Nylon Cable Ties

Catalog #	Size	Selling Unit
76003	4"	100/bag
76007	7"	100/bag
76011	11"	100/bag
76015	14½"	100/bag

- Raised ridges on bent tip for a sure grip
- Nylon toughness
- UL 94V-2 flammability classification
- Complies with military spec
- Self-locking, one-piece, low profile head conserves space
- Bent tip on all series of cable ties allows easier pick-up insertion, and pull-up
- V-shaped raised ridges on bent tip gives a sure grip and easier pull-up
- Engineered and manufactured for excellent performance
- For maximum comfort, smooth rounded edges will not cut hands or insulation

76003 - 4" Cable Tie

Tensile Strength: 18 lbs/8 kgs
Max Bundle Diameter: 1"
Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon

76007 - 7" Cable Tie

Tensile Strength: 50 lbs/22 kgs
Max Bundle Diameter: 1.75"
Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon

76011 - 11" Cable Tie

Tensile Strength: 50 lbs/22 kgs
Max Bundle Diameter: 3"
Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon

76015 - 14½" Cable Tie

Tensile Strength: 50 lbs/22 kgs
Max Bundle Diameter: 4"
Temperature: Rated from -40°F to 185°F
Flammability Rating: UL 94V-2
Material: Nylon

