

Contractors' CHOICE®

Wire Connectors - For Conventional Dry Splices

Product Specifications

Yellow Wing Connector

- Max Voltage: 300V or 600V
- Wire Range: Min #18/Max #10
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Tan Wing Connector

- Max Voltage: 600V
- Wire Range: Min #22/Max #10
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Red Wing Connector

- Max Voltage: 300V or 600V
- Wire Range: Min #18/Max #8
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Green Wing Connector

- For Grounding Terminals Only
- Wire Range: Min #14/Max #10
- Wire Type: Copper/Copper

Blue Wing Connector

- Max Voltage: 600V
- Wire Range: Min #14/Max #6
- Max Temp Rating: 105°C (221°F)
- Wire Type: Copper/Copper

Not suitable for wet applications.

See reverse side for a listing of wire combinations.

KING
INNOVATION®

Yellow Wing Connector

| Catalog # | Selling Unit |
|-----------|--------------|
| 67075 | Box of 100 |
| 67071 | Bag of 500 |




Tan Wing Connector

| Catalog # | Selling Unit |
|-----------|--------------|
| 67085 | Box of 100 |
| 67081 | Bag of 500 |



Red Wing Connector

| Catalog # | Selling Unit |
|-----------|--------------|
| 67095 | Box of 100 |
| 67091 | Bag of 500 |



Green Wing Connector

| Catalog # | Selling Unit |
|-----------|--------------|
| 27145 | Box of 500 |



Blue Wing Connector

| Catalog # | Selling Unit |
|-----------|--------------|
| 67115 | Box of 50 |
| 67111 | Bag of 100 |



- UL 486C and CSA 22.2 No. 188 Certified
- Tough ThermoPlastic, UL 94 V-2
Flame Retardant Shell

www.kinginnovation.com
(P) 800.624.4320
(F) 636.519.5410

Contractors' **CHOICE**[®]

Wire Connectors - For Conventional Dry Splices

Yellow Wing Connector - 300V Wire Combinations

Max. 3 #12

Min. 2 #16

Yellow Wing Connector - 600V Wire Combinations

Max. 3 #14

Min. 2 #18

Tan Wing Connector - 600V Wire Combinations

Max. 2 #10

Min. 3 #22

Red Wing Connector - 300V Wire Combinations

Max. 5 #12 Solid

Min. 2 #14

Red Wing Connector - 600V Wire Combinations

Max. 5 #14

Min. 3 #16

Green Wing Connector - Wire Combinations

Max. 2 #12

Min. 3 #14

Blue Wing Connector - 600V Wire Combinations

Max. 3 #8 w/1 #12

Min. 2 #10 w/1 #12

Please contact factory for a complete list of wire combinations.