


DryConn Waterproof Connectors


Insulation Displacement Connector for use with Utility Tracer Applications

INSTALLATION INSTRUCTIONS


1. Remove plastic tubing from side A and discard.




2. Place unstripped main conductor into side A.




3. Using finger pressure, press blade holders into housing until contact with main conductor is made.



4. Place unstripped tap conductor into side B (see image in step 2). Insert conductor until visible against stop on opposite side.



5. Using 8 in – 10 in (20.3 cm – 25.4 cm) Straight Jaw, Groove Joint Pliers, individually press blade holders into housing until blade holder is fully seated in housing. Verify top surface of blade holder is even or just below the top surface of the housing.



6. Remove sealant cover and discard.
7. Close housing, aligning conductors until housing lid is fully closed and latched.
8. Wipe excess sealant around conductors.
9. Do not reuse.



**Self Stripping -
No Need to Strip Wires!**

DRYCONN IDC CONNECTOR AQUA

Catalog #	Selling Unit
98405	Bag of 5

Product Specifications and Measurements


Max. Voltage:	50 V
Connector Size:	0.96 in x 1.73 in x 1.78 in (24.4 mm x 43.9 mm x 45.2 mm)
Wire Range:	#14-12 Solid/Stranded Copper #14-12 Steel Core Tracer Wire/CCS
Conductor O.D. Range:	0.121 in – 0.166 in (3.0 mm – 4.2 mm)
Sealant Temperature Rating:	-45°F to 400°F (-42°C to 204°C)

Construction

Electrical Contacts:	Tin-plated high conductivity brass
Housing:	High-impact polypropylene
Sealant:	Non-hardening viscous dielectric

Measurements:

A - 0.96 in	B - 1.73 in	C - 1.78 in
A - 24.4 mm	B - 43.9 mm	C - 45.2 mm



Features and benefits

- Waterproof and corrosion proof
- No need to strip conductor
- Install service line without cutting the main line
- Installs with hand tools
- One piece for easy installation
- Installs in one minute or less
- Designed for use with solid/stranded copper and steel core tracer wire with 0.030 in (0.7 mm) and 0.045 in (1.1 mm) thick insulation
- Wire range: #14-12 Solid/Stranded Copper and #14-12 Steel Core Tracer Wire/CCS
- High impact housing with user friendly design to prevent cuts or handling discomfort
- Use with low voltage TRACER lines under 50 volts
- Pre-filled with sealant
- Approved for direct bury

USA

Tel 800.624.4320
info@nVent.com

U.S. Patent 9,496,626 and additional Patents Pending apply.
All other trademarks, U.S. and Foreign Patents Apply. All Rights Reserved.



Our powerful portfolio of retail brands:

CADDY ERICO GARDNER BENDER KING INNOVATION